

15.6" Open Frame Touch Screen Monitor

ZLI56TMBCAP-OF



IP65 Front
IP40 Back



1920×1080



Tempered
Glass



800:1



250 Nits
(Optional)



15.6 inch Open Frame Touch Screen Monitor

Our 15.6 inch open frame touch screen monitor (Model No: ZLI56TMBCAP-OF) comes with 10-point multitouch technology, anti-glare treatment, and VESA mounting for easy use. The best part is that our 15.6-inch monitor comes with a high-quality display with 1920 x 1080 resolution, an anti-glare surface and a durable aluminum case with IP65 resistance.



Global Headquarter



Sales & Marketing Office



European RMA Office

Technical Specification

Product Name	15.6" Open Frame Touch Monitor
Model Number	ZL156TMBCAP-OF
IP Rating	IP65 Front / IP40 Back
Screen Diagonal (Inch/cm)	15.6/39.40
Active Display Area(cm)	34.41×19.35
Aspect Ratio	16:9
Physical Resolution	1920×1080
Maximum showable resolution	1920×1080
Colours Displayed	16.7M
Brightness (cd/m2)	250 Nits (Optional)
Contrast	800:1
Typical Reaction Time Tr/ Tf (ms)	15/15
Visual Angle Horizontal / vertical (°)	170/170
Backlight/Backlight Lifetime (hours)	LED/30,000
External Connectors	HDMI, DP, VGA, PC-Audio, USB, 12V DC-IN

Touch Technology	Projected Capacitive 10-point Multitouch
Touch Panel Drivers	Windows; Linux; Mac; Android
Touch Life (Contacts)	Unlimited
Surface Hardness	7H
Surface Treatment	Anti-Glare (Optional)
Glass Strengthening	Tempered Glass
Operating Temperature (°C)	-10 ~ +60
Humidity Range (RH)	10% - 90%
Net Weight (Kg)	3.05
Gross Weight (Kg)	4.20 (Incl.cartonage)
Housing Material	Aluminum front/back case
Housing(mm)L x W x H	241.59 × 392.16 × 48
Mounting	VESA 100
Power Indicator	Green LED
Power Supply	12V DC-Out

